



## HYBRID SOLAR INVERTER

**HI-8K-SL****Dual MPPT**

Two independent MPPT trackers with max 22A string current.

**Dual AC Outputs**

Smart load management with Main and Second output.

**Generator Compatible**

Supports generator input for backup power.

**Wide PV Range**

60Vdc-500Vdc MPPT voltage range with 12kW PV input capacity.

Technical Data	HI-8K-SL
<b>MODEL &amp; BATTERY</b>	
Nominal Battery Voltage	48Vdc
Battery Type	Lithium LiFePO4 / Lead-Acid / Flooded / User Defined
<b>AC INPUT</b>	
Nominal AC Input Voltage/Waveform	230Vac / Sinusoidal (Utility or Generator)
AC Input Range	90~280Vac (Appliances); 170Vac-280Vac (UPS)
Nominal Input Frequency	50/60Hz (Auto Detection)
AC Input Frequency Range	40-65±1Hz (>42 or <63±1Hz Comeback)
Max. Bypass Current	60Amp
Output Short Circuit Protection	Circuit Breaker
Transfer Time	15ms Typical (UPS); 25ms Typical (Appliances)
<b>AC CHARGER</b>	
Charging Algorithm	3-Step
Max. AC Charging Current	120Amp (@VI/P=230Vac)
Bulk Charging Voltage	56.4Vdc (AGM/Gel); 58.4Vdc (Flooded)
Floating Charging Voltage	54Vdc
Max. Hybrid Charging Current (Solar & Utility)	150Amp
<b>PV INPUT</b>	
Num. of Independent MPPT Tracker	2
MPPT Input Current	2*22Amp
Max. PV Array Power	12000W
Max. Solar Charge Current	150Amp
PV Array MPPT Voltage Range	60-450Vdc
Max. PV Array Open Circuit Voltage	500Vdc
MPPT Tracking Efficiency	99.9%
<b>INVERTER OUTPUT</b>	
Num. of Output Ports (Main & Second Output)	2
Rated Output Power (Main/Second Output)	8200W / 8200W
Max. Output Current (Main/Second Output)	34.8A / 34.8A
Surge Capacity	16400VA / 16400W for 5 Seconds
Output Voltage Waveform	Pure Sine Wave
Output Voltage	220/230/240 Vac ±5%
Output Frequency	50/60Hz ±1Hz
Peak Efficiency	94%
Low Voltage Cut-off Voltage	42Vdc
High Voltage Cut-off Voltage	63Vdc
Cold Start Voltage (When Only Connect with Battery)	46Vdc
No Load Power Consumption	70W @48Vdc
Parallel Capacity	NO
<b>GENERAL</b>	
Operating Temperature Range	10°C ~ 50°C
Storage Temperature	15°C ~ 60°C
Humidity	5% to 95% Relative Humidity (Non-Condensing)
Altitude	<2000m
Noise	<60dB
Protection Degree	IP21 (Indoor Only - implied)
Cooling Method	Intelligent Fan
Dimension (H*W*D)	605*440*143 mm
Weight	17.5 KG
Warranty	2 Years
<b>COMMUNICATION</b>	
Embedded Interface	RS232*1 / RS485*2 / Dry Contact
Work with WiFi & Bluetooth Monitoring Dongle	YES, by RS232
Work with Lithium Battery BMS	YES, by RS485
<b>CERTIFICATION</b>	
Certification / Standard	CE (IEC61000, IEC62109), IEC61683, IEC60068, RoHS